



Summit™ Lock Liner Compatibility

Manufacturer	Liner	Rating
Alps	Easy Liner	C**
Alps	GP	D
Alps	Thermoliner	C**
Alps	AK	C**
Daw	Cool Liner	C
Daw	Cool Liner with Strip	C**
ESP	Aegis Ultimate	D
Euro Intl	First Class	I
Medi	Akos TF	I
Medi	Relax	I
Medi	Sensitive	I
Ohio Willow Wood	Alpha AK	D**
Ohio Willow Wood	Alpha Max	C
Ohio Willow Wood	Alpha Original	A
Ohio Willow Wood	Alpha Spirit	C
Ossur	Comfort	B
Ossur	Dermo	B
Ossur	Original	B
Ossur	Sport	B
Ossur	Synergy	B
Ossur	Transfemoral	B
Ossur	Seal-In	A
Ossur	Wave	D
Otto Bock	Profile	I
Otto Bock	Simplicity	I
Otto Bock	Sirona	I
Otto Bock	TF	A
Silipos	Duragel	C
Steifeneder	Contex	B

A= Very Good, B=Good, C=Average,

D= Below Average, I=Insufficient Data

**Lock attachment needs to be glued to the limited stretch seam of these liners

This rating only refers to the compatibility of the liner with the Summit™

and LowPro Summit™ Locks, not the overall quality of the liner.

PLEASE READ PRIOR TO USE

Summit™ Fitting Tips

6mm thickness liners have proven to be the most effective with the Summit™ and LowPro Summit™ Locks, giving the lock a stable surface for attachment.

The Summit™ Lock and LowPro Summit™ Locks are ideal for LONG limb types.
For shorter limbs the locks can be used for rotational control in conjunction with a distal pin.

The liner must have a fabric backing for adhesion.

Test fitting is done without the lock to ensure sufficient socket suspension.

Fitting and casting is done without any extra room in the socket for the attachment to ensure proper compression within the socket.

During the fitting process ensure the patient is not pulling the tab through the lock excessively.
This will cause liner damage and irritation. The tab is designed to walk itself into position.

Ensure proper counter pressure and containment of the liner attachment within the socket.

Do not place liner attachment too high on the socket.

Coyote® Design Mfg. Inc.

7450 W. Lemhi Boise, ID 83709

Toll-Free Phone (800) 819-5980 Toll-Free Fax (866) 819-5980

Phone (208) 429-0026 Fax (208) 429-0028

www.coyotedesign.com